



# Benjamin Moore & Co.

## PROFESSIONAL COATINGS

MOORCRAFT

# Super Spec<sup>®</sup> Latex Vapor Barrier Primer Sealer 260

### Features

- ▲ Ideal for wallboard and plaster surfaces
- ▲ Forms a moisture vapor barrier and reduces heat loss
- ▲ Easy to apply; fast dry for quicker recoat
- ▲ Hides well with excellent hold out
- ▲ Good adhesion
- ▲ Alkali resistant
- ▲ Perm rating of less than 0.5. ASTM D1653

### General Description

A specially designed interior latex primer sealer that provides a film with low vapor permeability. This fast-drying, non-breathing primer-sealer acts as a moisture vapor barrier when applied on interior walls and ceilings.

### Recommended For:

For new or previously painted drywall construction, plaster, composition board, non-bleeding woods, and concrete.

### Limitations:

- Do not apply when air and surface temperatures are below 50° F (10° C).

### Product Information

#### Colors: —Standard:

260 00 White  
(May be tinted with up to 2.0 fl. oz. of Benjamin Moore Color Preview™ colorants per gallon.)

#### —Tint Bases:

Not available

#### —Special Colors:

Contact your Benjamin Moore & Co. representative

#### Certification:

Formulated without lead, mercury, or chromates.  
Formulated with non-photochemically reactive solvents.

#### Technical Assistance

Available through your local authorized independent Benjamin Moore & Co. dealer.  
For the location of the dealer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

#### Technical Data

White

Vehicle Type	Acrylic Blended Latex
Pigment Type	Titanium Dioxide
Volume Solids	27%
Theoretical Coverage At	450 Sq. Ft.
Recommended Film Thickness	
<i>Be sure to estimate the right amount of paint for the job. This will ensure proper coverage and minimize the disposal of excess paint.</i>	
Recommended Film Thickness – Wet	3.6 Mills
– Dry	1.0 Mills
Dry Time @ 77° F	30-60 Minutes
(25° C) @ 50% RH	2 Hours
– To Recoat	2 Hours
– To Hard Dry	2 Hours
Dries By	Evaporation, Coalescence
Viscosity	88 ± 2 KU
Flash Point (Seta)	None
60° Specular Gloss	Flat
Surface Temperature at application – Min.	50° F
– Max.	90° F
Thin With:	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon	10.5 lbs.
Storage Temperature – Min.	40° F
– Max.	90° F
Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 250 Grams/Liter</i>	

TDS260A

## Surface Preparation

Surfaces to be primed must be clean, dry, and free of wax, grease, dust, dirt, and mildew. Previously coated surfaces should be sound and tight adhering. All plaster surfaces must be thoroughly cured. Patch all holes and cracks with spackling compound. Apply Moorcraft Super Spec Latex Vapor Barrier Primer Sealer before and after filling nail holes, cracks, and other surface imperfections. Glossy areas should be dulled. Remove all peeling and scaling paint by scraping or use of power equipment.

Poured and precast concrete must be allowed to cure for 60 – 90 days; block construction should be allowed to cure for 30 – 60 days. All surfaces must be thoroughly brushed with stiff fibre bristles to remove loose particles.

**NOTICE:** Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For additional information, contact the USEPA/Lead Information Hotline at 1-800-LEAD-FYI.

## Primer/Finish Systems

For best hiding results, tint Moorcraft Super Spec Latex Vapor Barrier Primer Sealer to the approximate shade of the finish coat, especially when a significant color change is desired. **Special Note:** Certain custom colors require a Deep Color Base Primer tinted to a special prescription formula to achieve the desired color. Consult your dealer.

Benjamin Moore® offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease, crayon markings, hard glossy surfaces, galvanized metal, or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore dealer can recommend the right problem-solving primer for your special needs.

### Wood, New:

**Primer:** Moorcraft Latex Vapor Barrier Primer Sealer

**Finish:** Appropriate Benjamin Moore & Co. interior finish paint

### Wood, Repaint:

**Primer:** Moorcraft Super Spec Latex Vapor Barrier Primer Sealer

**Finish:** Appropriate Benjamin Moore & Co. interior finish paint

### Plaster/Drywall, New:

**Primer:** Moorcraft Super Spec Latex Vapor Barrier Primer Sealer

**Finish:** Appropriate Benjamin Moore & Co. interior finish paint

### Plaster/Drywall, Repaint:

**Primer:** Moorcraft Super Spec Latex Vapor Barrier Primer Sealer

**Finish:** Appropriate Benjamin Moore & Co. interior finish paint

### Masonry, New:

#### Rough or Pitted Masonry:

**Fill:** Moorcraft® Super Craft™ Latex Block Filler (285)

**Primer:** Moorcraft Super Spec Latex Vapor Barrier Primer Sealer

**Finish:** Appropriate Benjamin Moore & Co. interior finish

#### Smooth Poured or Precast Concrete:

**Primer:** Moorcraft Super Spec Latex Vapor Barrier Primer Sealer

**Finish:** Appropriate Benjamin Moore & Co. interior finish

### Masonry, Repaint:

**Primer:** Moorcraft Super Spec Latex Vapor Barrier Primer Sealer

**Finish:** Appropriate Benjamin Moore & Co. interior finish paint

## Application

Stir thoroughly before use. Apply 1 or 2 full even coats by brush, roller or spray gun.

**Spray, Conventional:** See **Thinning/Cleanup**

**Spray, Airless:** Fluid Pressure — 1,500 to 3,000 PSI;  
Tip — .017 Orifice; Filter — 60 mesh.

## Thinning/Cleanup

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents.

Clean brushes, rollers and other painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for more information on disposal options.**

## Environmental & Safety Information

**Contains: Crystalline Silica** that can cause cancer when in the respirable form (spray mist or sanding dust).

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust/particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**IN CASE OF SPILL:** Absorb with inert material and dispose of as specified under **Thinning/Cleanup**

**KEEP OUT OF REACH OF CHILDREN**

**Protect from freezing.**

**Material Safety Data Sheets available  
on request from your servicing dealer.**

