



SAFETY DATA SHEET

Product Name: ICYNENE PROSEAL™ B-SIDE RESIN

Section 1: Chemical, Product and Company Information

Product Name: ICYNENE PROSEAL™ B-Side Resin also known as MD-C-200™ V3
ICYNENE MD-C-200™ and ICYNENE PROSEAL™ are trademarks of Icyne Inc.

Product Code: ICYNENE PROSEAL™ B-SIDE RESIN

Product Use: Blend of polymeric resins and additives that react with polymeric methylene diisocyanate to create PROSEAL™ foam, a semi-rigid closed cell polyurethane foam for building and other construction insulation and protection. For professional and industrial use only.

Company Information: Icyne Inc., 6747 Campobello Rd., Mississauga, Ontario, L5N 2L7, Canada
Tel: 905.363.4040 Toll Free: 800.758.7325 Fax: 905.363.0102

Section 2: Hazards Identification

Classification
Acute Toxicity: oral, Category 4
Acute Toxicity: Skin, Category 5
Skin Corrosion/Irritation, Category 1A
Serious Eye Damage/Eye Irritation, Category 2B
Specific Target Organ Toxicity (repeated exposure) [central nervous system (CNS) and kidneys] – Category 2
Specific Target Organ Toxicity (single exposure) [central nervous system (CNS) and kidneys] – Category 2



Section 3: Composition/Information on Ingredients

Component	CAS No.	Wt %
1,1,1,3,3-Pentafluorobutane	406-58-6	13 – 30
Tris(1-chloro-2-propyl) phosphate	13674-84-5	7 – 13
1,1,1,2,3,3,3-Heptafluoropropane	431-89-0	1 – 5
Bis(3-dimethylaminopropyl)-n,n-dimethylpropandiamine	33329-35-0	1 - 10
N-cyclohexyl-methylcyclohexanamine	7560-83-0	1-7
Pentamethyldiethylenetriamine	3030-47-5	1-7

SAFETY DATA SHEET

Product Name: ICYNENE PROSEAL™ B-Side Resin

Section 4: First Aid Measures

- Eye:** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.
- Skin:** Clean exposed skin with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation:** Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Ingestion:** Get medical attention immediately. Wash out mouth with water. Move exposed person to fresh air. Can enter lungs and cause damage. Do not induce vomiting. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person.
- Notes to physician:** Adrenalin and similar sympathomimetic drugs should be avoided following exposure as cardiac arrhythmia may result with possible subsequent cardiac arrest. Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours as delayed pulmonary edema may develop.

Section 5: Fire Fighting Measures

- Flash Point:** Not Available
- Method Used:** Not Available
- Flammable Limits:**
- LFL:** Not Available
- UFL:** Not Available
- Extinguishing Media:** Carbon dioxide, dry chemical, foam. In case of large fires, water spray should be used. Use an extinguishing agent suitable for the surrounding fire.
- Explosion Hazards:** In a fire or if heated, a pressure increase will occur and the container may burst. In use, may form flammable/explosive vapor-air mixture if no proper ventilation is in place.
- Fire Hazards:** Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

SAFETY DATA SHEET

Product Name: ICYNENE PROSEAL™ B-Side Resin

Hazardous Combustion Products

Carbon dioxide, carbon monoxide, nitrogen oxides, Dense black smoke, Other potentially toxic fumes.

Fire Fighting Equipment:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6: Accidental Release Measures

Personal Precautions:

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment

Environmental Precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods for Cleaning Up:

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7: Handling and Storage

Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Recommended storage temperature (Min/Max): 23 - 30°C. If materials are received outside the recommended temperature, condition the materials for 24 hours before use. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in

SAFETY DATA SHEET

Product Name: ICYNENE PROSEAL™ B-Side Resin

unlabeled containers. Use appropriate containment to avoid environmental contamination. Make sure there is adequate ventilation to prevent localized vapor accumulation.

Section 8: Exposure Controls/Personal Protection

Engineering Controls

Use local exhaust ventilation to maintain airborne concentrations below the TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it. The local exhaust ventilation must be independent of HVAC system, such as furnace, air conditioning, etc. The ventilation equipment should be running during and after the installation process. HVAC system should be turned off during and 24 hours after the installation.

Respiratory Protection:

Sprayers and Helpers must always wear Supplied-Air Respirators with full-face protection (hood or full-face piece type) when spraying. When handling the foam product, it is essential that at a minimum workers were properly fit-tested NIOSH approved Air Purifying Respirator.

Skin Protection:

Sprayers and helpers must always wear chemically resistant gloves and full body protection to prevent skin contact. There should be no skin exposed during handling, processing or application of Icynene™ spray foam products.

Eye Protection:

Goggles or shield safety eyewear complying with an approved standard should be used when handling or spraying the foam products to avoid eye exposure to liquid splashes, mists or dusts.

Hands

Butyl Rubber, Nitrile Rubber and Neoprene Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling the foam chemical products.

Section 9: Physical and Chemical Properties

Physical State:

Brown liquid

Boiling Point:

Not Available

Vapour Pressure:

Not Available

Freezing Point:

Not Available

Vapour Density:

Not Available

Solubility in Water:

Not Available

VOC content

Not Available

Specific Gravity:

1.2

Odour:

Amine Odour

pH:

10.5-11.5

Viscosity:

250-450 cps at 25°C Brookfield Spindle #1 at 20 RPM

Coefficient of Water/Oil Distribution

Not Available

Section 10: Stability and Reactivity

SAFETY DATA SHEET

Product Name: ICYNENE PROSEAL™ B-Side Resin

<u>Stability:</u>	This product is stable under normal conditions. In use, it may form localized flammable/explosive vapour-air mixture if ventilation is inadequate.
<u>Incompatibility:</u>	Reactive or incompatible with the following materials: oxidizing materials, organic materials, metals, acids and alkalis, and isocyanates.
<u>Shelf-Life:</u>	Six months
<u>Hazardous Polymerization:</u>	Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11: Toxicological Information

Potential Acute Health Effects:

Ingestion	Harmful if swallowed
Inhalation	Irritating to respiratory system.
Eyes	Severely irritating to eyes. Risk of serious damage to eyes
Skin	Harmful and severely irritating to skin. May cause skin sensitization.

Potential Chronic Health Effects:

<u>Chronic Effects:</u>	Contains material that may cause target organ damage, based on animal data.
<u>Target Organs:</u>	Cardiovascular system, central nervous system
<u>Carcinogenicity:</u>	No known significant effects or critical hazards
<u>Mutagenicity:</u>	No known significant effects or critical hazards
<u>Teratogenicity:</u>	Contains material which can cause birth defects.
<u>Fertility Effect:</u>	No known significant effects or critical hazards
<u>Developmental Effects:</u>	No known significant effects or critical hazards

Section 12: Ecological Information/Environmental Fate

Aquatic Ecotoxicity: Not Available

Biodegradability: Not Available

<u>Environmental Effects:</u>	The majority of this product is intended to react with co-reactant polymeric diisocyanate MDI and form solid foam product staying in place of service. Little environmentally harmful chemicals will be released to the environment. This product may be harmful to the environment if accidentally released in large quantities.
--------------------------------------	---

Section 13: Spill, Leak and Disposal Procedures

Major Spill: Call Icynene Inc. (800) 758-7325. If transportation spill involved call CANUTEC (613) 996-6666

Minor Spill: Absorb the resin with sawdust or other absorbent. Scoop up solid absorbent for waste disposal. The area should then be washed down to dilute and remove the remaining traces of material.

Disposal Method: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of

SAFETY DATA SHEET

Product Name: ICYNENE PROSEAL™ B-Side Resin

environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14: Transport Information

TDG (TRANSPORTATION OF DANGEROUS GOODS) CLASSIFICATION: Not Regulated.

Section 15: Regulatory Information

CANADA:

CEPA (DSL)

All components are listed or exempted.

WHMIS:

D2A: Material causing other toxic effects (Very Toxic)

D2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and this MSDS (Material Safety Data Sheet) contains all the information required by the CPR.

Section 16: Other Information

References:

- Canadian Guide of the Law and Regulations of the Transportation of Dangerous Goods
- Controlled Products Regulations
- Manufacturer's Material Safety Data Sheets

Manufacturer Disclaimer:

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED ICYNENE EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE, DATA SHEETS FOR ICYNENE PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM ICYNENE. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO ICYNENE, MANUFACTURING MANAGER, PRODUCT SAFETY, AT THE ABOVE-NOTED ADDRESS.

PREPARATION INFORMATION:

Revision Version and Date: July 1, 2015

Prepared by: Icyne Inc.

Telephone: 1.800.758.7325

Health & Safety Certified Sprayer

Icynene spray foam insulation products have an excellent health and safety record spanning more than 350,000 projects over more than 25 years. Nonetheless, safe handling practices during and immediately following installation are required to eliminate the possibility of health effects from exposure to isocyanates. Asthma, other lung problems, and irritation of the nose and throat can result from inhalation of isocyanates. Direct contact with the skin and eyes can result in irritation. Different individuals will react differently to the same exposures; some will be more sensitive than others. Severe asthma attacks have been reported in some sensitized workers exposed repeatedly to isocyanates while not wearing proper protective equipment. Some reports indicate a reaction and sensitization can occur following a single, sustained occupational exposure to isocyanates without proper protective equipment above the OSHA permissible exposure limit. But sensitization might not occur immediately in some individuals. Consistent use of personal proper protective equipment to prevent exposure during spraying and within the 4 hour*-period after spraying is completed is critical to eliminating the health hazard. Once sensitization has occurred, a worker might not be able work safely with spray foam insulation again.

Sprayers, sprayer helpers, and anyone else present during spraying or within 4 hours* after spraying is complete: You must wear proper Personal Protective Equipment (PPE) at all times during spray, including full-body-coverage, chemical-protective clothing and a NIOSH-certified respirator with fresh air supply. While spraying and for 4 hours* after spraying is completed, no one must be allowed within 50 feet of the sprayed foam without wearing this type of PPE at all times. Adequate active, negative pressure ventilation (exhaust fans) of the job site must be in place during spray and for 4 hours* after spray is complete.

For installations of low VOC products Icynene Classic Max and Icynene ProSeal in the United States only, re-entry and re-occupancy of the job site is permitted after 4 hours* provided that ventilation rates are followed as recommended on this page.

Independent studies and third party toxicologist verification indicates that when the prescribed ventilation rates and periods are followed, Icynene spray foam insulation is safely cured.



RE-ENTRY AND RE-OCCUPANCY PERIODS

Times based upon ventilating during and after a spray application.

Ventilation Rate (Air Changes per Hour)	Re-entry period for sprayers, helpers, informed trade workers and contractors	Re-occupancy period for all others
At 0.3 ACH	24 hours	24 hours
At 1.0 ACH	12 hours*	24 hours
At 10.0 ACH	4 hours*	24 hours
At 40.0 ACH	4 hours*	4 hours*

* Twelve (12) and four (4) hour re-entry for trades applies to all Icynene products sold in the United States. Four (4) hour re-occupancy applies only to low VOC products (Icynene Classic Max and Icynene ProSeal).

Icynene Inc. 6747 Campobello Road
Mississauga, Ontario L5N 2L7 Canada

Ph: 1.800.758.7325 • ICYNENE.COM

SL-511 • Updated May 2015

 **ICYNENE**®
The Evolution of Insulation™